



# Classic softshell jacket in sporty design made of recycled polyester

Pleasantly soft 3-layer function material with TPU-membrane Wind- and waterproof (5,000 mm water column), breathable and permeable to water vapour

Seams not sealed

Inside made of micro fleece, mesh lining in the front

Stand-up collar

2 side pockets and 1 breast pocket with zips Full-length under-panel 2-way zip with chin cup Elastic cord on hem for width-adjustment

Zips: YKK

JN1171: lightly waisted

Fabric: Outer fabric (290 g/m²): 100%

polyester (recycled) Lining: 100% polyester

Country of origin: Bangladesch

Customs tariff number: 61023090

## Care instructions:



## Partner article:



Ladies' Softshell Jacket Art-Nr.: JN1171

#### Available colours

Available colours									
	s	M	L	XL	XXL	3XL			
Weight in g	665 g	700 g	745 g	785 g	830 g	885 g			
VPE	1/20	1/20	1/20	1/20	1/20	1/20			
(Pcs. per inner packaging									
/ pcs. per outer packaging									

Measurements in cm	S	М	L	XL	XXL	3XL
1/2 chest	54,00 cm	57,00 cm	61,00 cm	65,00 cm	69,00 cm	73,00 cm
1/2 bottom width	52,00 cm	55,00 cm	59,00 cm	63,00 cm	67,00 cm	71,00 cm
front length from shoulder	70,00 cm	72,00 cm	74,00 cm	76,00 cm	78,00 cm	80,00 cm
length back from shoulder	73,00 cm	75,00 cm	77,00 cm	79,00 cm	81,00 cm	83,00 cm
sleeve length	64,00 cm	66,00 cm	67,00 cm	69,00 cm	70,00 cm	73,00 cm

# Available colours









## **OEKO-TEX® Standard 100**

OEKO-Tex® CONFIDENCE IN TEXTILES STANDARD 100 15.0.70467 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100



## Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



# **Recycled Polyester**

PET bottles are recycled to create a new fashion. Plastic bottles are crushed, melted down and spun to yarn again, which is sometimes completely integrated into the production.



# Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.

Stand: 21.06.2024 - 04:49:53