



Classic softshell jacket in sporty design made of recycled polyester

Pleasantly soft 3-layer function material with TPU-membrane
Wind- and waterproof (5,000 mm water column), breathable
and permeable to water vapour

Seams not sealed

Inside made of micro fleece, mesh lining in the front

Stand-up collar

2 side pockets and 1 breast pocket with zips

Full-length under-panel 2-way zip with chin cup

Elastic cord on hem for width-adjustment

Zips: YKK

JN1171: lightly waisted

Fabric: Outer fabric (290 g/m²): 100% polyester (recycled)
Lining: 100% polyester

Country of origin: Bangladesch

Customs tariff number: 61023090

Care instructions:



Partner article:



Men's Softshell Jacket
Art-Nr.: JN1172

Available colours

	XS	S	M	L	XL	XXL
Weight in g	535 g	550 g	585 g	620 g	655 g	695 g
VPE (Pcs. per inner packaging / pcs. per outer packaging)	1/20	1/20	1/20	1/20	1/20	1/20

Measurements in cm	XS	S	M	L	XL	XXL
1/2 chest	48,00 cm	50,00 cm	52,00 cm	56,00 cm	60,00 cm	64,00 cm
1/2 bottom width	50,00 cm	52,00 cm	54,00 cm	58,00 cm	62,00 cm	66,00 cm
front length from shoulder	61,00 cm	62,00 cm	64,00 cm	66,00 cm	68,00 cm	70,00 cm
length back from shoulder	63,00 cm	64,00 cm	66,00 cm	68,00 cm	70,00 cm	72,00 cm
sleeve length	60,00 cm	61,00 cm	62,00 cm	63,00 cm	63,00 cm	63,00 cm

Available colours

black (blackC)
nautic-blue (293U)

brown (476C)
navy (296C)

graphite (432C)
red (200C)




OEKO-TEX® Standard 100

OEKO-Tex® CONFIDENCE IN TEXTILES STANDARD 100 15.0.70467 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100



Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



Recycled Polyester

PET bottles are recycled to create a new fashion. Plastic bottles are crushed, melted down and spun to yarn again, which is sometimes completely integrated into the production.



Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.