



Classic softshell jacket in sporty design made of recycled polyester

Pleasantly soft 3-layer function material with TPU-membrane Wind- and waterproof (5,000 mm water column), breathable and permeable to water vapour

Seams not sealed

Inside made of micro fleece, mesh lining in the front Stand-up collar

2 side pockets and 1 breast pocket with zips Full-length under-panel 2-way zip with chin cup Elastic cord on hem for width-adjustment

Zips: YKK

JN1171: lightly waisted

Outer fabric (290 g/m²): 100% Fabric:

polyester (recycled) Lining: 100% polyester

Country of origin: Bangladesch

Customs tariff number: 61023090

Care instructions:



Partner article:




Men's Softshell Jacket Art-Nr.: **JN1172**

Available colours


Available colours									
	xs	S	М	L	XL	XXL			
Weight in g	535 g	550 g	585 g	620 g	655 g	695 g			
VPE	1/20	1/20	1/20	1/20	1/20	1/20			
(Pcs. per inner packaging									
/ pcs. per outer packaging									

Measurements in cm	xs	S	М	L	XL	XXL
1/2 chest	48,00 cm	50,00 cm	52,00 cm	56,00 cm	60,00 cm	64,00 cm
1/2 bottom width	50,00 cm	52,00 cm	54,00 cm	58,00 cm	62,00 cm	66,00 cm
front length from shoulder	61,00 cm	62,00 cm	64,00 cm	66,00 cm	68,00 cm	70,00 cm
length back from shoulder	63,00 cm	64,00 cm	66,00 cm	68,00 cm	70,00 cm	72,00 cm
sleeve length	60,00 cm	61,00 cm	62,00 cm	63,00 cm	63,00 cm	63,00 cm

Available colours









OEKO-TEX® Standard 100

OEKO-Tex® CONFIDENCE IN TEXTILES STANDARD 100 15.0.70467 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100



Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



Recycled Polyester

PET bottles are recycled to create a new fashion. Plastic bottles are crushed, melted down and spun to yarn again, which is sometimes completely integrated into the production.



Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.

Stand: 28.05.2024 - 14:52:31