

# Stylish softshell jacket

Wind- and water-proof 3 layer functional fabric with PU membrane (2,000 mm water column) Non-taped seams Breathable (2,000 g/m²/24h) Soft, casual stretch fabric 2 side pockets with zipper 2 inner pockets JN1021: lightly waisted Elastic drawstring with stopper at hem

Fabric:

Fabilit

polyester, 10% elastane

Bangladesch

62024010

Outer fabric (270 g/m<sup>2</sup>): 90%

Country of origin:

Customs tariff number:

Care instructions:



Partner article:

Men's Softshell Jacket Art-Nr.: JN1020

Available colours

	S	М	L	XL	XXL			
Weight in g	467 g	474 g	503 g	543 g	562 g			
VPE	1/20	1/20	1/20	1/20	1/20			
(Pcs. per inner packaging								
/ pcs. per outer packaging								

Measurements in cm	S	М	L	XL	XXL
1/2 chest	45,00 cm	49,00 cm	53,00 cm	57,00 cm	62,00 cm
1/2 waist width	43,00 cm	47,00 cm	51,00 cm	55,00 cm	59,00 cm
1/2 bottom width	47,00 cm	51,00 cm	55,00 cm	59,00 cm	64,00 cm
front length from shoulder	62,00 cm	63,00 cm	65,00 cm	67,00 cm	69,00 cm
length back from shoulder	66,00 cm	67,00 cm	69,00 cm	71,00 cm	73,00 cm
sleevelength incl. shoulder	73,00 cm	74,00 cm	75,00 cm	76,00 cm	77,00 cm

Available colours



black (blackC) off-white (off-white) green (7481C) orange (1575C)

### Features



OEKO-TEX® Standard 100

OEKO-Tex® CONFIDENCE IN TEXTILES STANDARD 100 15.0.70467 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100

## Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



### Breathable-Permeable to water vapour

Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m2 within 24 hours. The higher this figure, the more breathable the textile is.



### Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.

Stand: 28.05.2024 - 23:33:07