James & Nicholson JN1022 Men's Softshell Vest



Stylish softshell vest

Wind and water-proof 3 layer functional fabric with TPU membrane (2,000 mm water column) Non-taped seams Breathable (2,000 g/m²/24h) Soft, sporty stretch fabric 2 side pockets with zipper 2 inner pockets JN1023: lightly waisted Elastic drawstring with stopper at hem

Fabric:

Outer fabric (270 g/m²): 90% polyester, 10% elastane

Country of origin:

Customs tariff number:

62114390

Bangladesch

Care instructions:



Partner article:

Ladies' Softshell Vest Art-Nr.: JN1023


Available colours

Available colours									
	S	М	L	XL	XXL	3XL			
Weight in g	377 g	402 g	433 g	465 g	502 g	531 g			
VPE	1/20	1/20	1/20	1/20	1/20	1/20			
(Pcs. per inner packaging									
/ pcs. per outer packaging									

Measurements in cm	S	М	L	XL	XXL	3XL
1/2 chest	52,00 cm	56,00 cm	60,00 cm	64,00 cm	68,00 cm	72,00 cm
1/2 bottom width	49,00 cm	53,00 cm	57,00 cm	61,00 cm	65,00 cm	69,00 cm
front length from	64,00 cm	66,00 cm	68,00 cm	70,00 cm	74,00 cm	77,00 cm
shoulder						
length back from	70,00 cm	72,00 cm	74,00 cm	76,00 cm	79,00 cm	83,00 cm
shoulder						

Available colours

azur (7451C) navy (289C) red (200C)



green (7481C) orange (1575C)

Features



OEKO-TEX® Standard 100

OEKO-Tex® CONFIDENCE IN TEXTILES STANDARD 100 15.0.70467 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100

Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



SHE

Breathable-Permeable to water vapour

Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m2 within 24 hours. The higher this figure, the more breathable the textile is.



Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.

Stand: 03.06.2024 - 09:11:31