James & Nicholson

JN1023 Ladies' Softshell Vest

Stylish softshell vest

Wind and water-proof 3 layer functional fabric with PU membrane (2,000 mm water column)
Non-taped seams
Breathable (2,000 g/m²/24h)
Soft, sporty stretch fabric
2 side pockets with zipper
2 inner pockets
JN1023: lightly waisted
Elastic drawstring with stopper at hem

Fabric:	Outer fabric (270 g/m²): 90% polyester, 10% elastane
Country of origin:	Bangladesch
Customs tariff number:	62114390

Care instructions:

Partner article:

Men's Softshell Vest
Art-Nr.: **JN1022**

Available colours

	S	M	L	XL	XXL
Weight in g	323 g	346 g	363 g	392 g	423 g
VPE (Pcs. per inner packaging / pcs. per outer packaging	1/20	1/20	1/20	1/20	1/20

Measurements in cm	S	M	L	XL	XXL
1/2 chest	45,00 cm	49,00 cm	53,00 cm	57,00 cm	62,00 cm
1/2 waist width	43,00 cm	47,00 cm	51,00 cm	55,00 cm	59,00 cm
1/2 bottom width	47,00 cm	51,00 cm	55,00 cm	59,00 cm	64,00 cm
front length from shoulder	58,00 cm	60,00 cm	62,00 cm	64,00 cm	66,00 cm
length back from shoulder	62,00 cm	64,00 cm	66,00 cm	68,00 cm	70,00 cm

Available colours

- azur (7451C)
- navy (289C)
- red (200C)
- black (blackC)
- off-white (off-white)
- green (7481C)
- orange (1575C)

Features

OEKO-TEX® Standard 100
OEKO-Tex® CONFIDENCE IN TEXTILES STANDARD 100 15.0.70467 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100

Softshell
Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.

Breathable-Permeable to water vapour
Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m2 within 24 hours. The higher this figure, the more breathable the textile is.

Water column from 1.500 mm
The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.